

M 3 6 M R C W A L L W A S H E R

Efficient wall washing with precise light placement



For designers who need a wall wash with floor to ceiling uniformity, comfortable lighting, and high efficiency, Selux offers the M36 MRC Wall Washer. This wall washer, has a regressed LED that is behind the baffle, creating a subtle presence in the overall design for offices, galleries, or hospitality spaces. M36 MRC Wall Washer is available in pendant, recessed, and surface mount.

A soft and even distribution

Equipped with the MRC Micro Reflector Cell Technology, it allows for exceptional optical control. The M36 MRC Wall Washer is a discrete, exceedingly low glare fixture with very narrow lateral throw which allows for precise light placement. A soft and even distribution illuminates the top of the wall to the floor, providing an excellent uniformity ratio. The M36 MRC Wall Washer is able to achieve excellent light distribution down an entire wall, floor to ceiling, with no glare to the viewer. The outside unlit corners bring new style to architectural lighting.

Small form factor that packs a punch

Don't let the small size of the M36 MRC Wall Washer fool you. It provides superior optical performance, creating even illumination with just the right amount of visual interest. Various sensor and emergency options are available. Depending on your needs, Selux offers custom lengths and custom configurations with unlit horizontal 90° inside and outside corners - no project is too complex for us! Mix and match the optical system of the M36 LED and M36 MRC Wall Washer for other various lighting tasks. Use the M36 MRC Wall Washer for a specific lighting scheme in combination with the M36 LED linear, for direct task lighting and a cohesive look.

M36 MRC WALL WASHER

Mounting	Recessed · Pendant · Surface
Construction	Extruded 6063-T6 aluminum construction · Easy access to optical chamber · Precision-designed optical chamber · Indirect optic choices, including wide batwing, allow for a range of indirect distributions
Light Engine	Luminaire efficacy up to 78lm/W · Up to 724lm per foot (direct) up to 1632lm per foot (direct/indirect)
CCT and CRI	2700K · 3000K · 3500K · 4000K; 90+ CRI
Driver	RoHS compliant constant current LED driver · Driver includes 0-10V dimming
Lifetime	L80 (10K) > 60,000hrs
Additional Options	Dimming 0-10V · In-line Fuse · Separate Switching · Emergency Options · Unlit Outside Corners 90° · Integration with standard M36 illuminated lengths available upon request

