

Oakwood Commons
Poughkeepsie, New York



project	Oakwood Commons
client	Oakwood Partners, LLC
architect	Optimus Architecture; Chipman Design Architecture; HDR Architecture & Engineering
landscape architect	William Fleming Associates, Inc.
general contractor	Kirchhoff-Consigli Construction Management
electrical planning	Jacobs Engineering Group Inc.
photographer	James Brigagliano; Lea Mueller

Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

Oakwood Commons Poughkeepsie, New York

Oakwood Commons is a mixed use business park set over 10 acres in Poughkeepsie, New York. It includes 110,000 square feet of 'A' class office space as well as ample retail and restaurant space.

In this particular application, the Stradex 700 was chosen to include the full cutoff option, thus reducing the amount of light pollution and increasing the efficiency of the lighting application. The MTR Bollards create an elegant entry for the office building, while the Ritorno accents the pedestrian walkways between and around the buildings.



Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

Ritorno Round Symmetric



Construction	Marine-grade stainless steel with bead-blasted finish arms · Stainless steel hardware · Drip groove around perimeter prevents rain marks on underside
Optic	Aluminum reflector shade painted White for maximum reflectivity
Light Source	LED in 3000K or 4000K · 80CRI minimum
Luminous flux	LED up to 6,606lm · Up to 62lm/W
Light Distribution	Type V
Mounting	Single Pole Mount · Wall Mount
Dimensions	Shade is Ø35 3/4" · Luminaire is 27 1/8" high · Pole height 10' through 16'
Finish	Tiger Drylac certified polyester powder coat finish
Options	GFCI · 0-10V dimming · HiLo Switching
Certificates	NRTL Damp Location · 5 Year LED Warranty · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish

Ritorno Round Asymmetric



Construction	Marine-grade stainless steel with bead-blasted finish arms · Stainless steel hardware · Drip groove around perimeter prevents rain marks on underside
Optic	Aluminum reflector shade painted White for maximum reflectivity
Light Source	LED in 3000K or 4000K · 80CRI minimum
Luminous flux	LED up to 6,923lm · Up to 65lm/W
Light Distribution	Type IV
Mounting	Single Pole Mount · Wall Mount
Dimensions	Shade is Ø34 1/4" · Pole height 10' through 16'
Finish	Tiger Drylac certified polyester powder coat finish
Options	GFCI · 0-10V dimming · HiLo Switching
Certificates	NRTL Damp Location · 5 Year LED Warranty · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish

Ritorno Square Asymmetric



Construction	Marine-grade stainless steel with bead-blasted finish arms · Stainless steel hardware · Drip groove around perimeter prevents rain marks on underside
Optic	Aluminum reflector shade painted White for maximum reflectivity
Light Source	LED in 3000K or 4000K · 80CRI minimum
Luminous flux	LED up to 6,923lm · Up to 65lm/W
Light Distribution	Type IV
Mounting	Single Pole Mount · Wall Mount

Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

Retrofit Kit



[en:] Interior - Exterior
 [en:] M36 - Selux + BIOS

Ritorno Mini Round



Construction Die cast aluminum arms · Drip groove around perimeter prevents rain marks on underside

Optic Heat-tempered convex lens protects lamp and reflector assembly

Light Source PAR 30 lamp · 39W or 70W

Light Distribution Type IV

Mounting Single Pole Mount · Wall Mount

Dimensions Shade is Ø24 1/8" · Luminaire is 31 3/16" high · Pole height 10' or 12'

Finish Tiger Drylac certified polyester powder coat finish

Options GFCI · Single Fusing

Certificates NRTL Wet Location · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish

Ritorno Mini Square



Construction Die cast aluminum arms · Drip groove around perimeter prevents rain marks on underside

Optic Heat-tempered convex lens protects lamp and reflector assembly

Light Source PAR 30 lamp · 39W or 70W

Light Distribution Type IV

Mounting Single Pole Mount · Wall Mount

Dimensions Shade is 24 1/8" · Luminaire is 31 3/16" high · Pole height 10' or 12'

Finish Tiger Drylac certified polyester powder coat finish

Options GFCI · Single Fusing

Certificates NRTL Wet Location · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish

