

50 Cannon Street
London, United Kingdom




client	50 Cannon Street
lighting designer	Despina at CBRE

50 Cannon Street London, United Kingdom

50 Cannon Street, located in the heart of the City of London, includes retail, restaurants, and a new entrance to a Bank station. With its recent comprehensive refurbishment, 50 Cannon Street shows off their new office with a brand new remodeled reception area.

With the modern environment and innovative remodeling, 50 Cannon street has created an inviting reception area with spectacular recessed lighting from Selux. The M100 LED was the perfect choice for creating an engaging lighting design – combining function, form, and efficiency.



Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

**50 Cannon Street
London, United Kingdom**

M100 - 4" wide linear lighting with a variety of optical options



M100 LED is constructed from 3-15/16" (100mm) wide extruded low copper aluminum housing and die cast endcaps · Exact cut lengths, lit corners, and project-specific Configurations may be specified · Impact-resistant lenses offer controlled lighting, protect against dust, and ensure high luminaire efficiency · Modular design allows for easy access to optical chamber · Available with LED Optimized White acrylic lens, Clear lens with Microprism inlay, or (Direct only) Symmetric LMO lens, 5° Asymmetric LMO lens, 20° Asymmetric LMO lens, and Batwing LMO. Selux offers multiple LED options including LEDs in static 2700K, 3000K, 3500K, or 4000K CCTs at 80+ and 90+ CRI, My White tunable white in 2700K - 6500K at 90+ CRI, BIOS SkyBlue® Technology at 83+ CRI, and RGBW. All LED options are within a 3-step MacAdam ellipse. Custom lumen outputs are also available upon request. M100 LED Regressed lighting offers the advantages a hidden light source and energy efficiency. Regressed lighting attractively fits into any kind of ceiling and can be applied for commercial, retail, and various other applications to transform general lighting into something special.

M100 Pendant



Construction	Extruded 6063-T6 aluminum construction · Easy access to optical chamber
Optic	LED Optimized White lens · Clear lens with Microprism inlay · LMO Indirect Wide Batwing · Direct only optics behind Satine diffuser: Symmetric LMO lens · 5° Asymmetric LMO lens · 20° Asymmetric LMO lens · Batwing LMO lens
Light Source	LEDs in static 2700K, 3000K, 3500K, or 4000K at 80+ or 90+ CRI · My White Tunable White 2700K - 6500K at 90+ CRI · RGBW upon request · Luminaire efficacy up to 113lm/W at 80+ CRI
Luminous flux	Up to 1171lm per foot (Direct or Indirect) and 2342lm per foot (Direct/Indirect) at 80+ CRI
Light Distribution	Direct · Indirect · Direct/Indirect
Mounting	Cable · Rigid Stem · Swivel Stem
Dimensions	3-15/16" wide (100mm) x 4" high (101mm) for Direct or Indirect, 6" high (152mm) for Direct/Indirect · Available in approximately 1-1/2" increments · Project-specific lengths are available upon request
Finish	Tiger Drylac certified polyester powder coat finish
Options	Piix™ MRC 1 Cell or 3 Cell modules can be integrated into the illuminated length · Damp location · In-line Fuse · Separate Switching · Emergency Circuit wiring · Corners (L, T, and X) · Configuration options · Multiple dimming options and integral sensors for energy savings
Certificates	NRTL Damp Location · 5 Year LED Warranty · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish · NGL 2013 · PIA 2013 · nLight enabled · enlightened enabled
[en:]	Interior
[en:]	M100 - Selux + BIOS

M100 Surface



Construction	Extruded 6063-T6 aluminum construction · Easy access to optical chamber
Optic	LED Optimized White lens · Clear lens with Microprism inlay · Optics behind Satine diffuser: Symmetric LMO lens · 5° Asymmetric LMO lens · 20° Asymmetric LMO lens · Batwing LMO lens
Light Source	LEDs in static 2700K, 3000K, 3500K, or 4000K at 80+ or 90+ CRI · My White Tunable White 2700K - 6500K at 90+ CRI · RGBW upon request · Luminaire efficacy up to 113lm/W at 80+ CRI
Luminous flux	Up to 1171lm per foot at 80+ CRI
Light Distribution	Direct
Mounting	Surface Mount

Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

M100 Recessed



Construction	Extruded 6063-T6 aluminum construction · Easy access to optical chamber
Optic	LED Optimized White lens · Clear lens with Microprism inlay · Optics behind Satine diffuser: Symmetric LMO lens · 5° Asymmetric LMO lens · 20° Asymmetric LMO lens · Batwing LMO lens
Light Source	LEDs in static 2700K, 3000K, 3500K, or 4000K at 80+ or 90+ CRI · My White Tunable White 2700K - 6500K at 90+ CRI · RGBW upon request · Luminaire efficacy up to 113lm/W at 80+ CRI
Luminous flux	Up to 1171lm per foot at 80+ CRI
Light Distribution	Direct
Mounting	Before and after drywall · T-bar · Slot Grid · Decoustic ceiling · Rotating Crossbar · Threaded Stud
Dimensions	3-15/16" wide (100mm) x 4" high (101mm) · Available in approximately 1-1/2" increments · Project-specific lengths are available upon request
Finish	Tiger Drylac certified polyester powder coat finish
Options	Piix™ MRC 1-Cell or 3-Cell modules can be integrated into the illuminated length · Damp location · In-line Fuse · Separate Switching · Emergency Circuit wiring · Corners (L, T, and X) · Chicago Plenum · Configuration options · Multiple dimming options and integral sensors for energy savings
Certificates	NRTL Damp Location · 5 Year LED Warranty · ARRA Compliant · RoHS Compliant · Union Made - IBEW Local 363 · ASTM and PCI for finish
[en:]	Interior
[en:]	M100 - Selux + BIOS

M100 Regressed



Construction	Extruded 6063-T6 aluminum construction · Easy access to optical chamber
Optic	LED Optimized White lens · Clear lens with Microprism inlay · Optics behind Satine diffuser: Symmetric LMO lens · 5° Asymmetric LMO lens · 20° Asymmetric LMO lens · Batwing LMO lens
Light Source	LEDs in static 2700K, 3000K, 3500K, or 4000K at 80+ or 90+ CRI · My White Tunable White 2700K - 6500K at 90+ CRI · RGBW upon request · Luminaire efficacy up to 109lm/W at 80+ CRI
Luminous flux	Up to 1130lm per foot at 80+ CRI
Light Distribution	Direct
Mounting	Before drywall · T-bar · Rotating Crossbar · Threaded Stud
Dimensions	3-15/16" wide (100mm) x 5" high (127mm) · Available in approximately 1-1/2" increments · Project-specific lengths

Modifications are possible due to the constant development and improvement of LED technology.

© Selux Corporation, Subject to technical modification 6.2017

Selux Corporation, 5 Lumen Lane, P.O. Box 1060, Highland, NY 12528

